

WISPRSM SkyScout2

GROUP 1 SUAS · POWER TO THE PRO

A U.S.-built, ultra-light multirotor built for rapid deployment, precision data capture, and reliable flight in demanding environments.

TECHNICAL SPECIFICATION



50 MPH

MAX WIND RATING

35 MIN

MAX FLIGHT TIME

12 MI

CONTROL RANGE

12 LB

MAX TAKEOFF WT

3.85 LB

MAX PAYLOAD

Software

Flight Controller Firmware	WISPR Flight Firmware custom ArduPilot build
Ground Control Software	WISPR Ground Control
Mission Planning Software	WISPR Ground Control and WISPR Cloud

GNSS

GNSS Receiver	Ublox ZED-X20P
RTK Compatible?	Yes, NTRIP or other RTCM services
PPK Compatible?	Yes, with WISPR Cloud Subscription
GNSS Band	All Bands
GNSS Constellations	All Constellations
IMU	Built-in 9-axis IMU

Smart Batteries

Voltage	22.8V
Capacity	4350mAh (99.18 Wh)
Battery Weight	1.4 lbs. (630g +/- 20g)
Charging Time	45 minutes

Case

Weight	17.6 lbs.
Weight Fully Loaded	37 lbs.
Exterior Dimensions	32.4" x 18.5" x 10.85" L x W x D
Exterior Cubic Volume	3.75 cu. ft.
Add'l Exterior Attachments	Roll Wheels, Handle

Drone

Maximum Sustainable Payload	3.85 lbs.
Max Flight Time to Battery Failsafe	No payload: 35 min. With 2.2 lb payload: 30 min (+/- 2 min)
Max Wind Rating	50 MPH
Collision Avoidance	Front, backwards, downwards
Terrain Follow Source	GNSS (high altitude) or LiDAR Range Finder (low altitude)
Folded Dimensions	4.5" x 10" x 17"
Fully Assembled Dimensions	14" x 24" x 24"
Diagonal Wheelbase	32.5" (props folded); 49" (props unfolded)
Battery Configuration	2 x WISPR Smart Batteries
Weight	5.3 lbs.
Max Takeoff Weight	12 lbs.
Max Speed	50 MPH
Operating Temperature	-4° F to 122° F
Propeller Size	18.2" x 5.9"
Orientation LED Light Covers	Red (Rear), White (Front)
Flight Controller	Cube Orange +
I/O Ports	MicroUSB (Flight Controller access) and USB-C (GPS logs storage)
Frame Type	Quad Copter
Made in America	Yes

Smart Controller

Smart Controller	Herelink
Display	5.5" LCD Screen
Roll Wheel Options	Single Roll Wheel
Video Transmission	1080p 30fps
Brightness	1000nits
Frequency	2.4Ghz over LTE
Range	12 miles
Antennas	2 x Antenna
Transmission Encryption	AES128